



## PD40-EM

Access Control

### SiPass Entro Prox Codoor – EN Standard

- 
- **All-in-one-reader**
  - **Integrated electromechanical lock**
  - **Mounted straight onto standard European lock case**

Prox Codoor is a system Prox reader for SiPass Entro with an integrated electromechanical lock. It is an "all-in-one reader" and is an efficient way to meet any indoor security needs. Since the reader is mounted straight onto a standard Euro lock case, you do not have to make any cuts in the door other than those required for the cables for power and communication.

PD40-EM is suitable for lock cases with a distance of 72 mm between the center of the door handle and the center of the lock cylinder. It's designed for European standard lock case, following DIN 18251 standard.

## Technical data

---

<b>PD40-EM</b>	
Card technology	125 kHz EM4102
Card read distance	Up to 3 cm with passive card
Interface to controller	BC-Link
Operating voltage	8 to 40 VDC 8 to 30 VAC
Current consumption	100 mA
Indicators	3 x LED (red/yellow/green)
Environment	Indoor use only
Operating temperature	0 to +50 °C
IP rating	IP30
Housing	Stainless steel housing with ABS base reader head
Colour	Stainless steel
Dimensions (W x H x D)	70 x 250 x 60 mm
Keypad	No
Approval	CE
Supplied with	Dropbox and a 5 metre cable

## Details for ordering

---

Type	Part no	Designation	Weight
PD40-EM	S24246-F8505-A1	Prox Codoor – EN Standard	1.0 kg

Issued by  
Bewator AB  
SE-171 24 Solna  
Sweden

[www.buildingtechnologies.siemens.com](http://www.buildingtechnologies.siemens.com)

© 2008 Copyright by  
Bewator AB, a Siemens company  
Data and design subject to change without notice.  
Supply subject to availability.

---

Document no. **A6V10081525**  
Edition 04.2008