



## CMT<sup>C</sup>1920

TFT Monitor

### 19" CCTV Colour TFT Monitor

TFT monitor specifically for CCTV applications


- High brightness and resolution for excellent image reproduction
- Optimized for CCTV applications
- Modern housing design and convenient operation via OSD menu

This SXGA high resolution TFT monitor is specifically designed for CCTV security applications. It has a BNC video input, an S-VHS input and a DVI input allowing connection to PC-based digital recorders. The monitor is further equipped with an audio input and includes integral loudspeakers.

The monitor is suited for demanding CCTV applications where bright rooms require very high screen brightness, high contrast and high resolution, plus an excellent view at all angles.

This TFT monitor offers numerous advantages over conventional CRT monitors, as it features flicker-free images, smaller desk space, detachable stand for easy wall mounting, low power consumption and above all, has up to 2 to 3 times the life span of CRT monitors.

## Dimension drawings



## Technical data

Resolution	SXGA, 1280 x 1024
Contrast ratio	550:1
Brightness	270 cd/m <sup>2</sup>
Colors	16,2 colors
Viewing angle Left/Right, Up/Down	70/70/75/60
Response time	8 ms
Power supply	100 – 240 V AC, 50/60 Hz
Power consumption	38 W
Scan frequency	H: 31k – 80 kHz, V: 50 – 75 Hz
Video input	<ul style="list-style-type: none"> <li>● 1 x Video in (BNC)</li> <li>● 1 x S-Video</li> <li>● 1 x DVI-I</li> </ul>
Input signal	Signal: RGB - 0.707 Vp-p / 75 ohm, H/V Sync – standard TTL input
DVI-I (PC)	SXGA, (1280 x 1024 Pixel, 60Hz)
DVI-I (DVI)	NTSC/PAL composite video, Connector:
Video	<ul style="list-style-type: none"> <li>● 1 BNC für CVBS- input,</li> <li>● 1 mini-din 4-pol. für S-video</li> <li>● Level: 1.0 Vp-p / 75 Ohm</li> </ul>
Audio	2 speakers
Input	<ul style="list-style-type: none"> <li>● 1 x Audio in</li> </ul>
Power	● 2 x 1 W
OSD control	colour, hue, brightness, contrast, sharpness, volume, language, scan (O/U),
OSD languages	English, German, French, Italian, Spanish, Polish, Czech, Swedish
Operating temperature	0 – 40 °C
Storage temperature	-20 – +60 °C
Housing	Plastic
Installation	VESA standard (4 x M4; 100 x 100 mm)
Dimensions, monitor only (W x H x D)	420 x 431.5 x 54.5 mm
Panel	DIN ISO 13406-2, class II
Approvals	CE UL, CUL, FCC-B

## Ordering data

Type	Order No.	Designation	Weight
CMTC1920	2GF3122-8AA	19" CCTV Colour TFT Monitor	5.0 kg