

Intrusion Panels  
 SPC Keypads  
 LCD Keypads



Type

Order No.

SPCK420.100

LCD keypad with 2x16 characters

S54543-F101-A100



The wired standard LCD keypad SPCK420 provides the user with an iconic Interface to control the security system. Its 32 character blue backlight display and keyboards allows control under all lighting conditions. Navigation of the intuitive menu system is achieved using the central Navigation key. The keypad also has soft keys and alphanumeric keys that allow contextual key operation and data input directly from the keypad.

Current consumption: minimum	55 mA (12 VDC)
Current consumption: maximum	90 mA (12 VDC)
Status LEDs	3
LCD Display	2 x 16 characters
Special function keys	Multi-dimensional navigation key and 2 soft keys
Operating temperature	+5 ~ +40 °C
Dimensions (W x H x D)	148 x 85 x 33 mm
Housing protection	IP30
Weight	0.200 kg
Data sheet	A6V38986, A6V10238974, A6V10238980

SPCK421.100

LCD keypad with 2x16 characters and card reader

S54543-F102-A100



The LCD keypad SPCK421 provides the same features as the standard wired keypad SPCK420, but has also the ability to set/unset using a proximity key fob. Proximity fobs have the advantage that they do not require batteries and negate the need for users to remember PIN's. When the system is configured to use the reader as setting / unsetting device, PIN entry is disabled during the entry timer.

Current consumption: minimum	90 mA (12 VDC)
Current consumption: maximum	110 mA (12 VDC)
Status LEDs	3
LCD Display	2 x 16 characters
Special function keys	Multi-dimensional navigation key and 2 soft keys
Operating temperature	+5 ~ +40 °C
Dimensions (W x H x D)	148 x 85 x 33 mm
Housing protection	IP30
Weight	0.200 kg
Data sheet	A6V38986, A6V10238974, A6V10238980