



## K42

Access Control

## Codelock with two codes

---

- One lock with two codes
- Sturdy construction for outdoor and indoor use
- Best selling codelock in the world

The K42 is the best-selling codelock in the world. It is compact and easy to use with a modern design that is suitable for either indoor or outdoor mounting. The K42 has a capacity of two four-digit codes. One can be used by residents while the other is used by the property caretaker, for example. All settings are made directly in the unit.

## Technical data

---

<b>K42</b>	
Operating voltage	12 to 24 VAC/DC
Current consumption	8 mA in standby
Inputs	Exit button requests with delay. Two separate for code disable.
Outputs	Voltage-free relay contact, max. 1 A, 28 VDC.
Opening time	1–30 sec.
Door capacity	1
Code capacity	Two four-digit codes
Operating temperature	-35 to +55 °C
Environment	Indoor or outdoor use (IP54 design). In very exposed locations, use SH2 or SH1 rain cover.
IP rating	IP54
Housing	Cast metal with stainless steel buttons and security lock
Colour	Grey
Dimensions (W x H x D)	80 x 140 x 40 mm

## Details for ordering

---

Type	Part no	Designation	Weight
K42	S24246-C3552-A1	Codelock with two codes	0.72 kg

Issued by  
Siemens Building Technologies  
Fire & Security Products GmbH & Co. oHG  
D-76181 Karlsruhe  
[www.buildingtechnologies.siemens.com](http://www.buildingtechnologies.siemens.com)

© 2009 Copyright by  
Siemens Building Technologies  
Fire & Security Products GmbH & Co. oHG  
Data and design subject to change without notice.  
Supply subject to availability.