



ASB6201

Access control

ConfigCard Creation Tool

to create configuration cards for the
AR618x-MX and AR6111-MX card readers

- **Easy-to-use software module to create configuration cards**
- **Compatible with the AR6201-MX Enrollment Reader**
- **Can program ISO14443-A and ISO15693 cards**

The ConfigCard Creation Tool program is used to create configuration cards which are used to program the AR618x-MX and AR6111-MX card readers.

Depending on the reader to be configured, the program makes it possible to create different configuration cards. The configuration cards will contain all the necessary information for the readers. These includes, for example, the “what” information should be read, “where” and “how”, such as the unique serial number of the card or an ID number from a sector/block.

In combination with the enrollment reader AR6201-MX the ConfigCard Creation Tool is able to read/write all cards according the ISO standards 14443-A and 15693.

Features

ASB6201 ConfigCard Creation Tool

- Compatible with the AR6201-MX enrollment reader
- Can program ISO14443-A and ISO15693 cards
- Windows style design for simple use
- Complete parameter settings for the AR618x-MX and AR6111-MX reader can be written to the configuration card
- Write data to multiple cards
- Ability to read Mifare cards with factory default keys and pre-defined keys

Description

The ConfigCard Creation Tool has been developed to keep the programming of multi-technology readers as simple and fast as possible.

Multi-technology readers like the AR618xMX offer the huge advantage that they can read cards with different ISO standards and even the information to be read can be configured. This includes e.g. the information on “what” is to be read, plus “where” and “how”. This information has to be programmed for such kinds of readers. In general, there are two possible ways to do this: with a terminal program connected to the reader or, even more simply and effective, with a configuration card.

Only a few steps are required to create a ConfigCard, and only seconds to program readers with such a ConfigCard. Due to the methodology a maximum time reduction for programming and re-programming will be achieved.

System Requirements

Hardware / PC

Operating system	Windows XP Windows 2000
Hard disk drive	Min. 25 MB free
Ports	COM port

Details for ordering

Type	Part no	Designation	Weight
ASB6201	P24246-P4400-A1	ASB 6201 – ConfigCard Creation Tool	0,1 kg

Issued by
Siemens Building Technologies
Fire & Security Products GmbH & Co. oHG
D-76187 Karlsruhe

www.sbt.siemens.com

Copyright © 2005

Data and design subject to change without notice.

Document no. **A24205-A335-B267**

Edition 07.2005