



## DC12

Access Control

## SiPass Entro Door controller

---

- **To connect all elements of a door**
- **Supports all standard modes from the basic one entry reader to two Entry-and-Exit readers for an anti-passback system**
- **Possible to connect readers that support Wiegand and Clock&Data standards**

The DC12 controls one door to be connected on the local RS485 bus to SR34i Segment Controller. The DC12 works with a variety of card readers (including magnetic stripe, proximity and hands-free) and keypads. It has a built-in display for status and error information.

## Technical data

---

<b>DC12</b>	
Dimensions (WxHxD)	250 x 128 x 54 mm
Colour	White
Current consumption	60 mA
Housing	Wall-mounted composite housing.
Inputs	Exit button request with delay. Door contact for indicating closed/open door. Tamper switch for internal control.
Interface	RS485 connection to SR34i and segment controller. Connection of readers via BC-link, Clock&Data or Wiegand.
Operating temperature	-35 to +50 °C
Operating voltage	8 to 40 VDC, 8 to 30 VAC.
Outputs	Voltage-free relay contact, max. 2 A, 30 V.

## Details for ordering

---

Type	Part no	Designation	Weight
DC12	S24246-C8502-A1	Door Controller	0.25 kg

Issued by  
Bewator AB  
SE-171 24 Solna  
Sweden

[www.buildingtechnologies.siemens.com](http://www.buildingtechnologies.siemens.com)

© 2008 Copyright by  
Bewator AB, a Siemens company  
Data and design subject to change without notice.  
Supply subject to availability.

---

Document no. **A6V10074305**  
Edition 04.2008